Uninformed Search

LAURA CORTÉS-RICO (www.cortes-rico.com)

Multimedia Engineering

Artificial Intelligence




What to do to find the **sequence of actions** that allow reaching the **goal (desirable state)**?

Artificial Intelligence


Uninformed Search

- 1. Search the sequence of actions.
- 2. Uninformed? The only available information is the definition of the problem.






















Problem Solver Agent Algorithm

```
function solve returns action
         inputs: perception
         static: seq: Sequence of actions, initially empty.
                    state: Current state
                    goal: Initially null
                    problem: Problem formulation, initially null
         state <- UPDATE-STATE (state, perception)</pre>
        if (seq is empty) then
                   goal <- GOAL FORMULATION(state)</pre>
                   problem <- PROBLEM FORMULATION(state, goal)</pre>
                  seq <- SEARCH (problem)</pre>
        end if
         action <- FIRST(seq)</pre>
         seq <- LEFT (seq)</pre>
         returns action
end function
```

Environment

- 1. Static
- 2. Completely observable
- 3. Discret
- 4. Sequence
- 5. Deterministic
- 6. Mono-agent

PROBLEM_FORMULATION



How is the agent initially?

Initial State



successor function: given a state, returns a set of ordered pairs <action, successor>

Actions

Initial State

How is the agent initially?


successor function: given a state, returns a set of ordered pairs <action, successor>

Is the current the **goal state**?

Initial State


Actions

Goal test



GLOSSARY

- **1.** <u>Initial State:</u> State in which the agent **starts**
- 2. Actions: Concrete execution. E.g. Move to left.
- **3.** <u>Successor Function:</u> Function that, **given a state**, returns a set of **ordered pairs** where each pair defines a possible action from the parameter state and the consequent state after executing the action.
- 4. <u>States space:</u> Set of all the possible states.
- 5. <u>Path:</u> State sequence connected by actions.
- 6. <u>Goal Test:</u> Function that determines if a given state is the goal state.
- 7. <u>Path cost:</u> Numeric cost associated with a path.
- 8. <u>Individual cost:</u> Associated to a given action.
- **9.** <u>Abstract:</u> Representing eliminating details.



"Toy problem" (Russell, 2008)

| A | В |
|---|---|
|---|---|



- States:
- Initial State:
- Successor Function:
- Goal test:
- Cost:


"Toy problem" (Russell, 2008)


|--|



- States: 2 x 2²: (A,B,CleA), (A,B, CleA), (A,B, CleA), (A,B, CleA), (A,B, CleA), (A,B, CleB), (A,B, CleB), (A,B, CleB), (A,B, CleB)
- Initial State: Any of the 8 possible.
- Successor function: <action,successor> donde acción Left, Right, Clean.
- Goal test: Is the state (A,B,CleA) or (A,B, CleB)?
- Cost: Each action costs 1.


"Toy problem": 8-Puzzle (Russell, 2008)






- States:
- Initial State:
- Successor Function:
- Goal test:
- Cost:


"Problema de juguete": 8-Puzzle (Russell, 2008)





- States: All possible configurations: 9!
- Initial State: Any of the 9!
- Function successor:<action,successor> Possible actions: move the hole up, down, left, right.
- **Goal test:** Is the board ordered? (The desirable state may change)
- **Cost:** Each movement costs 1.

"Toy problems": 8 Queens (Russell, 2008)



- States: 64x63x62x61x60x59x58x57 different configurations of the board with 8 Queens.
 Initial State: Any of the previous.
- Function successor: <action,successor>
 Possible actions: Move queen N to the position (x,y).
- Goal test: State with 8 Queens on the board, with none attacking other. (<u>92 options</u>)
- **Cost:** Each movement costs 1.

Real world problems

Route finding (Russell, 2008)

- States: Each state obviously includes a location (e.g., an airport) and the current time. Furthermore, because the cost of an action (a flight segment) may depend on previous segments, their fare bases, and their status as domestic or international, the state must record extra information about these "historical" aspects.
- Initial state: This is specified by the user's query.
- Actions: Take any flight from the current location, in any seat class, leaving after the current time, leaving enough time for within-airport transfer if needed.
- Transition model: The state resulting from taking a flight will have the flight's destination as the current location and the flight's arrival time as the current time.
- Goal test: Are we at the final destination specified by the user?
- Path cost: This depends on monetary cost, waiting time, flight time, customs and immigration procedures, seat quality, time of day, type of airplane, frequent-flyer mileage awards, and so on.

Real world problems

Turist

Travel guide

VLSI

Robotic navigation

Assignment

- 1. Breadth-first search (*Búsqueda primero en anchura*)
- 2. Uniform-cost search (*Búsqueda de costo uniforme*)
- 3. Depth-first search (Búsqueda primero en profundidad (y hacia atrás))
- 4. Depth-limited search (*Búsqueda de profundidad limitada*)
- 5. Iterative deepening depth-first search (*Búsqueda primero en profundidad con profundidad iterativa*)
- 6. Bidirectional search (*Búsqueda bidireccional*)

- Explanation
- Example
- Advantages
- Disadvantages

References

González, E. (2015) Agentes Racionales y SMA, Notas de clase. Pontificia Universidad Javeriana.

González, J. (n.d.) *Inteligencia Artificial. Tema 1: Introducción*. Recuperada de: <u>https://ccc.inaoep.mx/~jagonzalez/AI/Sesion1 Introduccion.pdf</u>Julio 2017.

Russell, S. & Norvig P. (2008) Inteligencia Artificial: Un Enfoque Moderno. Pearson, Prentice Hall.

Winston, P. (1992) Artificial Intelligence, 3ra edición. Addison-Wesley Publishing Company. Recuperado de: <u>http://courses.csail.mit.edu/6.034f/ai3/rest.pdf</u> Julio 2017.